

## SLI022025WW PW




CE

---

Power	<b>5,5 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>660 lm (360°)</b>	Colour of light	<b>WW</b>
Beam angle	<b>120 °</b>	Degree of protection (IP)	<b>IP20</b>

---



 User manual

Technical data:

Code	SLI022025WW_PW
Power	5,5 W
Nominal current	34 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	6 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.5
Useful luminous flux*	660 lm (360°)
Luminous flux**	480 lm (360°)
Lamp efficacy	120 lm/W
Colour of light	WW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	83x40 mm
Mounting hole	66 mm
Weight	0.1 kg
For use	Inside
Assembly method	Recessed
Application	INT
Number of pieces on the packaging	20 pcs.
Made in	PRC



\*applies to the LED source used, \*\*Luminaire luminous flux