

LED GLS




---

Power	<b>8,5 W</b>	Voltage	<b>24 V</b>
Luminous flux**	<b>1030 lm (360°)</b>	Colour of light	<b>NW</b>
Beam angle	<b>230 °</b>	UGR	<b>20 lm</b>
Socket	<b>E-27</b>	Degree of protection (IP)	<b>IP20</b>


---



 Declaration of Conformity

Technical data:

Code	WOJ+14615
Power	8,5 W
Nominal current	500 mA
Voltage	24 V
Energy efficiency class	E
Energy consumption	9 kWh/1000h
Frequency	50HZ Hz
Power factor	0.68
Useful luminous flux*	1030 lm (360°)
Luminous flux**	1030 lm (360°)
Lamp efficacy	121 lm/W
Colour of light	NW
Beam angle	230 °
UGR	20
RA	>80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Socket	E-27
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	60 x 107 mm
Weight	0.042 kg
For use	Inside
Application	Inside
Number of pieces on the packaging	10 pcs.
Made in	PRC
Other	24V AC(50Hz)/DC



\*applies to the LED source used, \*\*Luminaire luminous flux