

iQ-LED

Kanlux

IQ-LEDDIM A60

Světelný zdroj LED



[V] 220-240 AC	[Hz] 50	SMD	360° Φ _{use}	+ ellipse ≤ 6x MacAdam	Ra 80	≥40000
25000 [h]	Hg		CE	EAC	UK CA	



IQ-LEDDIM A60 7,3W-WW



	PON [W]	[W]	[lm] Φ _{use}	Tc [K]	[°]	E27	E
IQ-LEDDIM A60 7,3W-WW	33722	7,3	60	806	2700	220	E
IQ-LEDDIM A60 7,3W-NW	33723	7,3	60	806	4000	220	E
IQ-LEDDIM A6013,6W-WW	33726	13,6	100	1521	2700	220	E
IQ-LEDDIM A6013,6W-NW	33727	13,6	100	1521	4000	220	E

Kanlux IQ-LED znamená fotobiologickou bezpečnost, šetrnou teplotu barev očím a spolehlivost. Nyní to vše v nové verzi E27 - verze Kanlux IQ-LEDDIM navíc lze stmívat. Žárovky Kanlux IQ-LED poskytují plný komfort používání a bezpečnost, což potvrzuje certifikát TÜV Rheinland.

- Materiál: plast
- Materiál difuzoru: plast

iQ. LED

Kanlux

IQ-LEDDIM A60

Světelný zdroj LED



IQ-LEDDIM A60 7,3W-WW




IQ-LEDDIM A60 7,3W-NW




IQ-LEDDIM A6013,6W-WW



IQ-LEDDIM A6013,6W-NW



IQ-LEDDIM A60 7,3W



IQ-LEDDIM A60 13,6W