



| | | | |
|-----------------|----------------------|--------------------|---------------|
| Power | 2 W | Voltage | 230 V |
| Luminous flux** | 200 lm (360°) | Colour temperature | 3000 K |
| Colour of light | WW | Beam angle | 55 ° |
| Socket | GU10 | | |



 Declaration of Conformity

Technical data:

| | |
|------------------------------|---------------|
| Code | WOJ+14669 |
| Power | 2 W |
| Nominal current | 20 mA |
| Voltage | 230 V |
| Energy efficiency class | F |
| Energy consumption | 2 kWh/1000h |
| Frequency | 50HZ Hz |
| Power factor | 0.4 |
| Useful luminous flux* | 150 lm (90°) |
| Luminous flux** | 200 lm (360°) |
| Lamp efficacy | 75 lm/W |
| Luminous intensity | 125 cd |
| Colour temperature | 3000 K |
| Colour of light | WW |
| Beam angle | 55 ° |
| RA | >80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Socket | GU10 |
| Dimension (AxBxC) | 35x48 mm |
| Weight | 0.027 kg |
| For use | Inside |
| Application | INT |
| Made in | PRC |

